

## CONTAINERIZED WIRELINE TRUCK UNIT



### KEY FEATURES:

- ✓ Standard 20' ISO container foot print wireline truck unit suitable to be mounted on 6 x 4 / 4 x 4 chassis
- ✓ Single or dual drum is available upon requirement.
- ✓ Suitable for both day and night operation with well illuminated cabin and outside flood lights
- ✓ Operator cabin equipped with dual air conditioner, workbench and an emergency door.
- ✓ Unit equipped with close loop hydrostatic transmission. Close loop hydraulic system is ideal for logging & MPLT operations
- ✓ Drums suitable for different slickline wire sizes range 0.092 – 0.160" and braided line 3/16" with more than 20,000 ft. wire capacity
- ✓ Line speed varies 3 ft./min to 1900 ft./min
- ✓ Line pull max 8000 lbs.
- ✓ Powered by 111 Hp Zone-2 diesel engine power pack.
- ✓ Truck engine PTO driven units are also available in Rig safe spec.
- ✓ Benchmark ATEX approved measuring head and data acquisition system (Combined depth, tension and speed)
- ✓ Hydraulic driven air conditioner for operator cabin is suitable for desert climate condition. Suitable up to 60° ambient temperature.
- ✓ Hydraulic weight indicator and both Digital and mechanical depth counter
- ✓ ATEX rated electrical air conditioner in special cases
- ✓ Measuring wheels are suitable to handle wires 0.092 to 0.160" and up to 1/4". Metric and Feet unit wheels are available upon choice.

### PAINTING:

- ✓ Sand blasted to SA 2-1/2 grade and apply 3 coat paint by customer specified colour.

### OPTIONS:

- ✓ Onboard PCE (BOP and Stuffing box) control unit
- ✓ Equipped with 10K Psi high pressure test unit with chart recorder. Unit is pneumatically operated with HP/LV and LP/HV combination pumps.

