

WIRELINE CRANE TRUCK UNIT



KEY FEATURES:

- ✓ Crane truck unit enables to lift the whole lubricator assembly and BOPs on the well head. This unit supports the containerized wireline truck's lifting requirements.
- ✓ Crane is 4 section 92' (28 m) long boom and 28 ton lift capacity @ 5 ft. radius, and @ 10 m radius with 97 ft. vertical height, 3.8 ton lift capacity.
- ✓ Crane swing system is 372° non-continuous rotation.
- ✓ Equipped with open loop hydrostatic transmission for the crane functions. Powered by 84 Hp Zone-2 diesel engine power pack.
- ✓ Truck engine PTO driven units are also available in Rig safe spec.
- ✓ Foldable ladder with hand rails on both side of the deck
- ✓ Crane can be operated from the rear crane deck. Engine throttle and emergency stop button also available on the operator platform
- ✓ Lubricator racks for 3", 5" and 7" are on the truck deck.
- ✓ BOPs can be fixed on the threaded stubs on the truck deck.
- ✓ X-Over stand
- ✓ Rear ladder with tool box for stem bars mechanical jars etc.
- ✓ Tool boxes are available on top of the deck and underneath the deck
- ✓ Air compressor with 1300 lpm @ 8 bar
- ✓ Equipped with 10K Psi high pressure test unit with chart recorder. Unit is pneumatically operated with HP/LV and LP/HV combination pumps.

PAINTING:

- ✓ Sand blasted to SA 2-1/2 grade and apply 3 coat paint by customer specified colour.

OPTIONS:

- ✓ Fluid recovery system with hose reel and control panel
- ✓ Hydraulic 10kVA 230V 50hz 1 phase generator

